




PIN CONNECTIONS FROM PARALLEL CABLE:

PIN15 (USE FOR LANE 1 SIGNAL)
PIN 23 (USE FOR LANE 1 GROUND)
PIN 13 (USE FOR LANE 2 SIGNAL)
PIN 22 (USE FOR LANE 2 GROUND)
PIN 12 (USE FOR LANE 3 SIGNAL)
PIN 24 (USE FOR LANE 3 GROUND)
PIN 10 (USE FOR LANE 4 SIGNAL)
PIN 25 (USE FOR LANE 4 GROUND)





JELLYFIRE ENGINEERING – COPYRIGHT



3RD ANGLE PROJECTION

MARK ALL EQUIPMENT &
DETAILS, WHERE PRACTICAL,
WITH DRAWING NUMBER

TOLERANCES FOR MACHINED WORK:

ONE DECIMAL PLACE: ±0.3
TWO DECIMAL PLACES: ±0.1
THREE DECIMAL PLACES: ±0.02
NOMINAL DIMENSIONS ±0.5
SURFACE FINISH: 3.2 µm

UNLESS OTHERWISE STATED

TOLERANCES FOR NON MACHINED WORK:

SHEET METAL/FABRICATION: ±1.0
ALL OTHER DIMENSIONS ±0.5
ANGULAR TOLERANCE: ±0.5°
SURFACE FINISH: AS SPECIFIED

UNLESS OTHERWISE STATED

TITLE: TRACK MOUNTING ASSEMBLY		
SCALE: DO NOT SCALE	MATERIAL: VARIOUS	
DATE: 08.11.14	QUANTITY: 1 – OFF	
SHEET: 1	OF: 1	DRAWN: C. JELFS
DRG. No. #	REMARKS: #	